



AFLEX 3006

Flexible Current Probes (6000A) for PROVA 6830A

Features:

- Flexible current probes (3pcs. per set) for **PROVA 6830A** only.
- Range selection: **Manual** (600A, 6000A).

Electrical Specifications:

Please refer to **PROVA 6830A+AFLEX 3006**.

General Specifications: (3pcs. per set)

Probe Length:	3006-36	36 in / 920 mm
Minimum Bending Diameter:		35mm
Connector Diameter:		23mm
Cable Diameter:		14mm
Cable Length from Probe to Box:		1700mm
Cable Length from Box to Output:		1700mm
Range selection:		Manual (600A, 6000A)
Dimension (Box):		130mm(L) x 80mm(W)x 43mm(H) 5.1"(L) x 3.1"(W) x 1.7"(H)
Battery:		Powered by power analyzer
Operating Temperature:		-10°C to 85°C
Operating Humidity:		15% to 85% RH
Altitude:		up to 2000M
Storage Temperature:		-20°C to 85°C
Storage Humidity:		15% to 85% RH
Weight:		430g per pc. 3pcs. per set

PROVA INSTRUMENTS INC.

Add: 6F-2, No. 129, Lane 235, Pao-Chiao Road, Shin-Tien District,
New Taipei City 23145, TAIWAN

Tel: 886-2-89191255

E-mail: prova@ms3.hinet.net

Fax: 886-2-89191489

Website: www.prova.com.tw