

PROVA 3009S

Flexible Current Probes (1200A)



Electrical Specifications:

Please refer to **PROVA 6830A+3009S**.

Features:

- Flexible current probes (3pcs. per set) for **PROVA 6830A** power analyzer only.
- Range selection: **Manual (120A, 1200A)**.
- **3P4W, 3P3W, 1P2W, 1P3W**.



General Specifications: (3pcs. per set) Indoors use

Probe Length:	18 in / 477mm
Max. Conductor Diameter:	130mm (approx.)
Min. Bending Diameter:	16mm
Connector Diameter:	12.3mm
Cable Diameter:	8.5mm
Cable Length from Probe to Box:	1700mm
Cable Length from Box to Output:	1700mm
Range selection:	Manual (120A, 1200A)
Dimension (Box):	63.2mm (L) x 40.3mm (W)x 28.5mm (H) 2.5" (L) x 1.6" (W) x 1.1" (H)
Battery:	Powered by power analyzer
Operating Temperature:	0°C to 50°C
Operating Humidity:	15% to 85% RH
Altitude:	up to 2000M
Storage Temperature:	-20°C to 60°C
Storage Humidity:	15% to 75% RH
Weight:	300g per pc., 3pcs. per set
Accessory:	Users manual x 1

PROVA

PROVA INSTRUMENTS INC.

Add: 6F-2, No. 129, Lane 235, Pao-Chiao Road,
Shin-Tien District, New Taipei City 23145,
Taiwan

Tel: 886-2-89191255

Fax: 886-2-89191489

E-mail: prova@ms3.hinet.net

www.prova.com.tw